

L I F T P R O D U C T S S P E C I F I C A T I O N S

HULK[®] SERIES LIFT AND TURN



Design Highlights

- Hand-held NEMA 4X Push Button with 10' Straight Cord
- Maintenance Strut
- Self Lubricating Bushings
- Wire Braided Hydraulic Hoses
- Solid Steel Legs with Hard Chromed Pins
- Pre-wired Power Unit with UL Approved Panel
- Velocity Fuses on All Cylinders to Prevent Uncontrolled Descent
- Polyethylene Reservoir Allows Easy Visual Check of Oil Level or Steel Reservoir with Dip Stick
- 1 HP Single Phase, 115 VAC Control Valve
- Meets or Exceeds the ANSI MH29.1 Standard for Industrial Scissors Lifts

Available Options

- Up Travel Limit Switch
- Foot Switch with Cover - NEMA 1
- In Motor Warning Beeper and Flashing Light on a Post X 60" High or Wall Mounted Bracket
- Hydraulic Powered Turntable with Push Button Control for Forward and Reverse, Plus Adjustable Speed with Flow Controls
- Increased Horsepower Available
- Manual Lowering Valve Located at Power Pack
- 1 HP Air/hydraulic Power Unit with Air Lever Valve or Air Foot Valve and 10' of Hose
- 1 HP 3 Phase Available
- Portability with Casters
- Stainless Steel
- Accordion Bellow - Yellow/black 4 Sides of Base
- Special Color
- Other _____

Project Information

Job Name _____
 Address _____
 General Contractor _____
 Distributor _____
 Model _____ Quantity _____ Voltage/Phase _____

HULK[®] SERIES LIFT AND TURN

L I F T P R O D U C T S S P E C I F I C A T I O N S

Model No.	Travel [in]	Capacity [lb]	Standard Platform & Base Frame [in]	Max. Turntable Size [in]	Lowered Height [in]	Raised Height [in]	Raise Lower Time (sec)	Ship Weight [lb]
KLT24-2MT	24	2,000	24 x 36	36 x 36	10	34	18	674
KLT24-4MT		4,000	24 x 36	36 x 36	12	35	25	860
KLT36-2MT	36	2,000	24 x 48	48 x 48	10	46	24	1,051
KLT36-4MT		4,000	24 x 48	48 x 48	12	48	48	1,142
KLT48-2MT	48	2,000	24 x 72	48 x 72	11	59	35	1,640
KLT48-4MT		4,000	24 x 72	48 x 72	12	60	70	1,700
KLT59-2MT	59	2,000	36 x 88	48 x 88	11	70	40	2,048
KLT59-4MT		4,000	36 x 88	48 x 88	12	71	80	2,310

