

Serco Blackout™ Dock Shelter

Model BDS-S



Facilities face greater challenges today regarding environmental control at the loading dock. Maintaining consistent temperature control, avoiding energy loss, effectively sealing varying trailer configurations, and meeting regulatory requirements are real issues. Additionally, air ride suspension and intermodal trailers create more abrasive movement on dock shelters. The Serco Blackout™ model BDS-S Dock Shelter is specifically designed for the most demanding applications.



Serco exclusive UHWR™ (Ultra High Wear Resistant) fabric features superior wear resistance. Tested and certified to **40,000+ abrasion cycles** which is up to **ten times** the abrasion resistance of the competitive fabrics tested. (Reference Serco fabric comparison)

- ① Exclusive S-900DD DryDock® Integral system effectively blocks moisture infiltration from the top of trailer.
- ② Exclusive Hinge Guard™ seals off hinge gap around swing out doors, blocking air and light from entering the facility.
- ③ Exclusive UHWR (Ultra High Wear Resistant) fabric on top and bottom wear panels where heaviest trailer abrasion occurs.
- ④ Exclusive LightBlockr™ connector curtain blocks air and light infiltration at overlap of side and head curtains.
- ⑤ Structural, rigid head frame acts as a canopy while translucent top cover allows increased visibility and operating light.
- ⑥ Exclusive roll-formed, galvanized steel framing extends product life and is superior to wood construction.
- ⑦ Foam-filled side members provide protection from impact by off-center trailers.



DRYDOCK® MOISTURE SEALING SYSTEM

- Integral to the Blackout Dock Shelter to automatically position and seal the top of the trailer
- High-resilient foam core protected by three layers of durable coated fabric
- Canopy style rigid head frame increases structural integrity while translucent head member allows operating light
- Weighted side covers provide extra protection for the dock area
- Services trailers 12'-9" to 13'-6" high



HINGE GUARD™ GAP SEALING SYSTEM

- Integral to the Blackout Dock Shelter to automatically position and seal the trailer door hinge gaps
- High Molecular Weight Polyethylene (HMWPE) material capable of withstanding harsh weather conditions and high cycle traffic.
- Hinge Guard specifically shaped and sized to interface with swing out door trailers of varying configurations.
- Attached securely with industrial hook and loop for easy replacement



ENTRE//MATIC

Entrematic
1612 Hutton Dr., Suite 140
Carrollton, TX 75006
800.933.4834
www.sercoentrematic.com

Entrematic reserves the right to change specifications and designs without notice and without incurring obligations. Entrematic products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Entrematic as word and logo are registered trademarks belonging to Entrematic Group AB or other companies controlled by the same organization. All rights reserved.

©Entrematic Group AB 2016. All rights reserved. Printed in USA Form # SCB-SHB0-0116