

Lift and Turn

LOADWARRIOR® SERIES

LIFT PRODUCTS SPECIFICATIONS

2,000 AND 4,000 LBS. CAPACITIES



Design Highlights

- Hand-held NEMA 4X Push Button with 10' Straight Cord
- Maintenance Strut
- Self Lubricating Bushings
- Wire Braided Hydraulic Hoses
- Solid Steel Legs with Hard Chromed Pins
- Pre-wired Power Unit with UL Approved Panel
- Velocity Fuses on All Cylinders to Prevent Uncontrolled Descent
- Polyethylene Reservoir Allows Easy Visual Check of Oil Level or Steel Reservoir with Dip Stick
- 1 HP Single Phase, 115 VAC Control Valve
- Meets or Exceeds the ANSI MH29.1 Standard for Industrial Scissors Lifts

Available Options

- Up Travel Limit Switch
- Foot Switch with Cover - NEMA 1
- In Motor Warning Beeper and Flashing Light on a Post X 60" High or Wall Mounted Bracket
- Hydraulic Powered Turntable with Push Button Control for Forward and Reverse, Plus Adjustable Speed with Flow Controls
- Increased Horsepower Available
- Manual Lowering Valve Located at Power Pack
- 1 HP Air/hydraulic Power Unit with Air Lever Valve or Air Foot Valve and 10' of Hose
- 1 HP 3 Phase Available
- Portability with Casters
- Stainless Steel
- Accordion Bellow - Yellow/black 4 Sides of Base
- Special Color
- Other _____

Project Information

Job Name _____

Address _____

General Contractor _____

Distributor _____

Model _____ Quantity _____ Voltage/Phase _____

1612 Hutton Drive, Suite 140 ● Carrollton, TX 75006, USA ● Tel: 800-933-4834 ● Fax: 972-389-4769 ● Email: sales@sercocompany.com ● www.sercocompany.com

A continuing research program is in effect at Serco. We reserve the right to incorporate product improvement at any time without prior notice.

© 2006 4Front Engineered Solutions, Inc.

Lift and Turn

LOADWARRIOR® SERIES

LIFT PRODUCTS SPECIFICATIONS

2,000 AND 4,000 LBS. CAPACITIES

Model No.	Travel [in]	Capacity [lb]	Standard Platform & Base Frame [in]	Max. Turntable Size [in]	Lowered Height [in]	Raised Height [in]	Raise Lower Time (sec)	Ship Weight [lb]
SLT24-2MT	24	2,000	24 x 36	36 x 36	10	34	18	674
SLT24-4MT		4,000	24 x 36	36 x 36	12	35	25	860
SLT36-2MT	36	2,000	24 x 48	48 x 48	10	46	24	1,051
SLT36-4MT		4,000	24 x 48	48 x 48	12	48	48	1,142
SLT48-2MT	48	2,000	24 x 72	48 x 72	11	59	35	1,640
SLT48-4MT		4,000	24 x 72	48 x 72	12	60	70	1,700
SLT59-2MT	59	2,000	36 x 88	48 x 88	11	70	40	2,048
SLT59-4MT		4,000	36 x 88	48 x 88	12	71	80	2,310

